



activTek

INDUCT 500

SINGLE ROOM AIR SYSTEM



2017 Space Technology
Hall of Fame Inductee

description

- Compact, self contained, natural air treatment system
- Discreet internal mounting
- No cleaning required
- ActivePure® Technology
- Convenient power cord

applications

- Installs inside of the ductwork of “Stand-Alone” or typical “In-Wall” air handler units
- Hotel rooms
- Motel rooms
- Offices

the technology

The activTek INDUCT 500 utilizes tested ActivePure® Technology to substantially reduce odors, visible smoke in the air, and treat contamination on surfaces. Designed to be installed inside the ductwork of an in-wall heating and air conditioning unit, INDUCT 500 is compact, self-contained, and requires no cleaning. Covers up to 500 square feet.

Professional installation recommended. Our proprietary ActivePure® Technology uses light waves and a catalytic process to produce scrubber ions that remove dust particles from the air. Our Certified Space Technology continuously protects and purifies the air, and attacks contaminants on all surfaces.*

*Published scientific studies conducted on behalf of activTek by Dr. James Marsden at Kansas State University demonstrated that activTek's ActivePure® Technology substantially reduces microbial populations on surfaces. The study's results are being provided solely for informational purposes. The study's results have not been reviewed by the FDA, EPA or any other governmental agency. Our products are not medical devices and are not intended to diagnose, treat, or cure any disease. We make no claims and no claims should be inferred as to the efficacy of our products to sanitize, disinfect or kill germs or other antimicrobials.

specifications

INDUCT 500	9960043 • 9960042 (ozone free)	
electrical	Input Voltage: 15VDC, .1 Amps, 100 – 240 VAC, 50/60 HZ	Current: 5 Watts – Switching Power Supply
mechanical	retainer clip included	
dimensions	10.38" L x 2.25" W x 1.25" H	28.37cm L x 5.72cm W x 3.175cm H
weight	2.9 lbs.	1.3 kilograms
hvac air blower	250 SCFM recommended air flow	
ozone production	0.40 ppm maximum with ozone replaceable UV bulb • 0.00 ppm with ozone-free replaceable UV bulb	
coverage	Up to 500 sq. ft.	
warranty	Limited 3 year warranty	