



# activTek INDUCT 750

## DUCT MOUNTED SYSTEM



2017 Space Technology  
Hall of Fame Inductee



### description

- Duct or plenum installed natural air system
- Discreet or concealed installation
- 100/277 volt optional installation
- UV bulb monitoring indicator included
- Low maintenance – no cleaning required

### applications

- Installs into any HVAC system up to 3 tons or 1500 CFM with accessible ducts
- Residential homes
- Apartments
- Small offices
- Elevators

### the technology

The activTek INDUCT 750 substantially reduces odors, visible smoke in the air, and microbial populations on surfaces\*, utilizing the patent pending ActivePure® Technology. ActivePure consists of a special UV light and photocatalyst target, creating an Advanced Oxidation Process containing several friendly oxidizers. Our proprietary

ActivePure® Technology uses light waves and a catalytic process to produce scrubber ions that remove dust particles from the air. Our Certified Space Technology continuously protects and purifies the air, and attacks contaminants on all surfaces.\*

\*Published scientific studies conducted on behalf of activTek by Dr. James Marsden at Kansas State University demonstrated that activTek's ActivePure® Technology substantially reduces microbial populations on surfaces. The study's results are being provided solely for informational purposes. The study's results have not been reviewed by the FDA, EPA or any other governmental agency. Our products are not medical devices and are not intended to diagnose, treat, or cure any disease. We make no claims and no claims should be inferred as to the efficacy of our products to sanitize, disinfect or kill germs or other antimicrobials.

### specifications

<b>INDUCT 750</b>	US40659B • US40668B (ozone free)	
<b>electrical</b>	Inpute Voltage: 100/277 VAC, 50/60 HZ	Current: .17A 17 Watts
<b>mechanical</b>	UV bulb monitoring system install	safety interlock switch installed
<b>dimensions</b>	9.62" H x 9.62" W x 7.48" D	24cm L x 24cm W x 19cm D
<b>weight</b>	3 lbs.	1.2 kilograms
<b>max temp</b>	<200°F	
<b>coverage</b>	Up to 750 sq. ft.	
<b>warranty</b>	Limited 3 year warranty	